

ICS 47.020

U 01

CB

CB/T 2999—2020

CB/T 2999—2010

**Basic requirements and evaluation methods of design conditions
for ship design organizations**

2020 - 04 - 24

2020 - 10 - 01

		III
1		1
2		1
3		1
3.1		1
3.2		1
3.3		1
3.4		2
3.5		2
3.6		2
3.7		2
4		2
4.1		
4.2		
5		3
6		5
6.1		
6.2		
6.3		
6.4		
7		6
7.1		
7.2		
7.3		

9.2	60	
9.3	60	
9.4		60
9.5	30	
9.6	30	
9.7	60	
10		 13
10.1		
10.2		100
10.3	50	
10.4	50	

GB/T 1.1—2009
CB/T 2999—2010

, CB/T 2999—2010

a		4.1	4.2.1	2010	4.1	4.2.1
b				2 2010		2
c	“ ”					2010
	7.4 7.5.3 7.5.4					
d	“ ” “ ”	7.5	7.6			
e	“ ”	9.2	2010	7.6		
f					8	2010

1

2

GB/T 19001

BC

IBC

IGC

GC

CSR

HCSR

3

3.1

ship design

1(

		a
		b
		c
		a
		b 20 m
		SPAR

2

		1	$L \geq 220\text{ m}$	$L \leq 150\text{ m}$	$L \leq 60\text{ m}$
		2	HCSR $L \geq 150\text{ m}$	HCSR, $L \leq 100\text{ m}$	HCSR, $L \leq 60\text{ m}$
		3	5000TEU	3000TEU	500TEU
		4	HCSR $L \geq 150\text{ m}$	HCSR $L \leq 100\text{ m}$	HCSR $L \leq 60\text{ m}$
		1	/	$L \leq 100\text{ m}$	$L \leq 70\text{ m}$
		2			

6.4.2

6.4.2.1

7

10

A

6.4.2.2

800

70 %

7

7.1

5

	25	16	8
		10	5

7.5.2 F•r9đp•%E9c%+ÜXÇ 1VÓ#ŠD %÷1V 2024E`CÂŸñ r9.pf" r9đH A,s a +Üf <)• )FY†Tcæ P—#Ÿ € %BYW• q&`Cí 6

7

	a	10	30	5	
	b	GB/T 19001		30	
	c	30		20	3
	d				

8

		a 60 60 2 b 30 6 24 60 2 1 1 0.5 c 40 5 d 40 2
		a 30 60 2 b 15 3 60 3 12 2 1 0.5 c 40 5 d 40 2
		a 15 60 2 b 60 2 8 0.5 1 c 40 5 d 40 2
		a 30 60 2 b 15 3 60 3 12 2 1 0.5 c 40 5 d 40 2
		a 20 60 2 b 60 10 60 2 1 0.5 c 40 5 d 40 2
		a 10 60 2 b 60 5 60 2 1 0.5 c 40

9

9.1

	60	60	60
30	30	60	300
210			

9.2 60

Ř

b

10

c

10

9.4

60

a

b

c

d

5

9.5

30

a

b

c

d

5

9.6

30

a

b

c

d

5

a

30

9.7

60

9.7.1

5

12

9.7.2

